

description -

H.264/Hybrid Series

The DVRH series DVR still competes with the best models out on the market today. This DVR continues to be packed with features you would think you could only find on the more expensive units. With true VGA, equal video outputs, alarm in/output, audio in/output, USB mouse supports for user-friendly operation and programmable call monitor sequencing, this DVR will impress you.



specifications -

Audio in/out	4/8/16ch line input, 1 ch output
Compression Format	H.264/MJPEG
Dynamic IP & DDNS	Yes
Firmware Upgrade	USB Flash drive port
Motion Detection	Motion detection setup by grid
Network Interface	10/100 base-T Ethernet (RJ-45)
Remote operation	Monitor, Playback, Record, System Setup, Dome Control, Archive
RS485	Terminal Block
Storage Backup	x3 USB 2.0 ports or DVD-RW
Video Resolution	Up to 1280x1024
Signal System	NTSC
Operating Temp.	20°F to 104°F
Power Consumption	AC 100~240V
Dimensions (WxHxD)	16.25 x 2.25 x 17.5 in.
Weight	10 ~ 15.4 lbs

features -

- Free DDNS Server for use with dynamic IP addresses
- VGA, 1 BNC Main Monitor, 1 BNC Call Monitor
- USB mouse Support for user-friendly operations
- True VGA on Main Monitor
- IR Remote control included
- H.264 and MJPEG compression
- Triplex + operation enabling simultaneously view live playback while continuing to record & network transfer
- 250 GB HD standard (Upgradeable to 500GB, 750GB, 1TB, 1.5TB, 2TB)
- Up to 16 channels of audio in
- Remote monitoring, recording, playback, change settings and PTZ control via Ethernet and/or Internet.
- Real Time Live display
- Built-in DVD-RW for video exporting
- USB 2.0 port for video exporting
- Easy software upgrade via Network, USB, or DVD-RW
- Configurable normal and event recording frame rate and picture quality by channel or globally by simple record.
- Email notification of alarm events
- Each camera configuration is programmable for camera settings, frame rate, picture bit rate, alarms, motion detection.
- Multiple built-in dome camera protocol through RS485 (including Pelco D, Pelco P)
- Automatic camera detection (Plug & Play)
- Digital Zoom 2x in live mode
- Covert camera operation
- Programmable recording priority, motion detection alarms, and scheduling
- Programmable call-monitor switching sequence
- Up to 30 seconds pre-alarm recording
- Multiple language on-screen menus
- Password to secure installation authorization
- Network software supports static IP, DHCP, PPPoE and DDNS
- Works with dynamic & static IP addresses

Discontinued - DVRH CONT.

- Free DDNS Server for use with dynamic IP addresses
- VGA, 1 BNC Main Monitor, 1 BNC Call Monitor
- USB mouse Support for user-friendly operations
- True VGA on Main Monitor
- IR Remote control included
- H.264 and MJPEG compression
- Triplex + operation enabling simultaneously view live playback while continuing to record & network transfer
- 250 GB HD standard (Upgradeable to 500GB, 750GB, 1TB, 1.5TB, 2TB)
- Up to 16 channels of audio in
- Remote monitoring, recording, playback, change settings and PTZ control via Ethernet and/or Internet.
- Real Time Live display
- Built-in DVD-RW for video exporting
- USB 2.0 port for video exporting
- Easy software upgrade via Network, USB, or DVD-RW
- Configurable normal and event recording frame rate and picture quality by channel or globally by simple record.
- Email notification of alarm events
- Each camera configuration is programmable for camera settings, frame rate, picture bit rate, alarms, motion detection.
- Multiple built-in dome camera protocol through RS485 (including Pelco D, Pelco P)
- Automatic camera detection (Plug & Play)
- Digital Zoom 2x in live mode
- Covert camera operation
- Programmable recording priority, motion detection alarms, and scheduling
- Programmable call-monitor switching sequence
- Up to 30 seconds pre-alarm recording
- Multiple language on-screen menus
- Password to secure installation authorization
- Network software supports static IP, DHCP, PPPoE and DDNS
- Works with dynamic & static IP addresses