

description -



3 Dimension Controller

3 Dimension PTZ Controller. Controls camera functions such as Pan, Tilt, Zoom, and Focus. Sets and calls camera preset positions. Activates pre-programmed group presets, tour and group sequences.



specifications -

Connector Type	RJ-11 6-pin modular
Keyboard Keypad	PC Keyboard button, numeric keypad and camera function keys
Operating distance	4000 ft (1029 m) on 24 AWG wire
Joystick	3-axis, vector solving, with twisting, return-to-center head.
LCD Display	2-line x 20 character alphanumeric LCD display with green backlight.
Communication	RS-485
Protocol	Pelco P & D (baud rate selectable)
Operating Temp.	32°F to 113°F (0°C - 45°C)
Power Consumption	12VDC/150mA
Dimensions (WxHxD)	15 x 4 x 6 in. (376 x 112 x 145 mm)
Supplied Voltage	12 VDC (10-14V), 140mA
Weight	Approx. 3 lbs., 1.3 Kg

features -

- Recalls up to 255 cameras from one keyboard.
- Multiple protocol supported in each channel (Pelco-D, DRX-502)
- Preset position control.
- Variable manual control speed from 1 deg/sec - 90 deg/sec
- Maximum speeds are proportional to zoom ratio.
- Recalls programmed guard tours from each dome camera.
- Recalls Auto-Swing from selected dome camera.
- Built-in graphic LCD monitor with green screen.
- Programmable user preferences (preset, tour, group, etc.)
- User password support.
- Supported DVR protocol (need to be modified)
- Easily upload programmed data via serial communication port of computer.
- Slave keyboard support.