

4 MP WDR Mini Dome Network Camera



Key features

- 4MP , 2688*1520
- IP66 Weather-Proof Protection
- 2.8mm Fixed Lens
- Up to 30ft IR range
- 120dB Wide Dynamic Range
- 3D Digital Noise Reduction
- Full HD1080p + 1520p Video
- Built-in Microphone, Audio Output, Alarm IO
- DC12V & PoE

Specifications

MIPFVD4	
Camera	
Image sensor	1/3" Progressive Scan CMOS
Min. illumination	0.01Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter time	1/3 s to 1/10,000 s
Lens	2.8mm @ F2.0
Day & night	IR cut filter With auto switch
Digital noise reduction	3D DNR
Wide dynamic range	WDR 120dB
Backlight compensation	Yes, Zone Configurable
Angle Adjustment	Pan: -30° ~ 30°, Tilt: 0 ~ 75°, Rotation: 0
Compression standard	
Video compression	H.264 / MJPEG / H.264+
H.264 compression profile	Main profile
Bit rate	32 Kbps ~ 16 Mbps
Audio Compression	G.711/G.722.1/G.726/MP2L2
Audio Bit rate	64Kbps(G.711) / 16Kbps(G.722.1) / 16Kbps(G.726) / 32-128Kbps(MP2L2)
Image	
Max. image resolution	4MP , 2688*1520
Frame rate	60Hz: 20fps (2688×1520), 30fps (1920×1080), 30fps(1280×720) 50Hz: 20fps (2688×1520), 25fps(1920×1080), 25fps(1280×720)
Image settings	Rotate Mode, Saturation, Brightness, Contrast, Sharpness adjustable by client software or web browser
Network	
Network storage	NAS (Support NFS,SMB/CIFS), ANR
Alarm trigger	Motion detection, Tampering alarm, Network disconnect, IP address conflict, Storage exception
Protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
System compatibility	ONVIF (PROFILE S, PROFILE G), PSIA, CGI, ISAPI
Security	One-Key Reset, Flash-Prevention, Dual Stream, Heartbeat, Mirror, Password Protection, Privacy Mask, Watermark, IP Address Filtering, Anonymous Access
Interface	
Communication interface	1 RJ45 10M / 100M ethernet port
General	
Operating conditions	-22 °F ~ 140 °F(-30 °C ~ 60 °C), humidity 95% or less (non-condensing)
Power supply	DC12V ± 10%, PoE (802.3af)
Power consumption	Max. 5W
protection	IP66, IEC60068-275EH, 20J; EN50102, up to IK08
IR range	Approx. 30ft
Dimensions	3.9" x 3.8" x 2" (99.3×96.7×52.8 mm)
Weight	1.32 lbs (600g)

Dimensions

